

Application number. 09/813,420
Amendment dated August 26, 2004
Reply to office action of February 26, 2004

PATENT

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings of claims in the application:

Listing of Claims:

Claim 1 (cancelled)

Claim 2 (original) A radio receiver, comprising:

an amplifier configured to receive and amplify an intermediate frequency modulated signal having in-phase and quadrature phase DC components;

an analog-to-digital converter configured to receive the amplified intermediate frequency modulated signal and convert it to a digital signal;

a demodulator operable to demodulate the digital signal;

DC offset calibration means coupled to the demodulator operable to provide in-phase and quadrature phase DC offset correction signals to compensate for the in-phase and quadrature phase DC components at the input of the amplifier; and

The radio receiver of claim 1, further comprising:

delay measurement means coupled to the demodulator operable to determine a delay vector characterizing the in-phase and quadrature phase DC components.

Claim 3 (original) The radio receiver of claim 2, wherein the delay vector is used by the DC offset calibration means to provide a digital representation of the in-phase and quadrature phase DC offset correction signals.

Claim 4 (original) The radio receiver of claim 3, further comprising:
a first digital-to-analog converter configured to receive a in-phase component of the digital representation of the in-phase DC offset correction signal for mixing with an in-phase signal and an intermediate frequency carrier signal;

a second digital-to-analog converter configured to receive a quadrature phase component of the digital representation of the quadrature phase DC offset correction signal for mixing with a quadrature signal and the intermediate frequency carrier signal; and

Application number. 09/813,420
Amendment dated August 26, 2004
Reply to office action of February 26, 2004

PATENT

a summer operable to subtract the mixed quadrature phase signal and quadrature phase DC offset correction signal component from the mixed in-phase signal and in-phase DC offset correction signal to provide a DC compensated intermediate frequency modulated signal at the input of the low noise amplifier.

Claim 5 (original) A radio receiver, comprising:
a receiving stage configured to receive a radio signal;
a first mixer stage operable to downconvert the radio frequency signal to a first intermediate frequency in-phase signal and a first intermediate quadrature phase signal;
first and second low pass filters configured to receive and low pass filter the first intermediate frequency in-phase and quadrature phase signals;
a second mixer stage operable to upconvert the filtered first intermediate frequency in-phase and quadrature phase signals and provide a second intermediate frequency in-phase signal and a second intermediate frequency quadrature phase signal;
a summer operable to subtract the second intermediate frequency quadrature phase signal from the second intermediate frequency in-phase signal to provide an integrated signal;
an automatic gain control stage coupled to the summer and operable to amplify the integrated signal;
an analog-to-digital converter operable to convert the amplified integrated signal to a digital signal;
a demodulator operable to demodulate the digital signal; and
delay measurement means for determining a delay vector from inputs of the low pass filters to an output of the demodulator.

Claim 6 (original) The radio receiver of claim 5, further comprising:
a DC offset calibrator coupled to the delay measurement means;
an in-phase digital-to-analog converter coupled between the DC offset calibrator and the second mixer stage; and

Application number. 09/813,420
Amendment dated August 26, 2004
Reply to office action of February 26, 2004

PATENT

a quadrature phase digital-to-analog converter coupled between the DC offset calibrator and the second mixer stage,

wherein the in-phase digital-to-analog converter is operable to provide an in-phase DC offset compensation signal for the automatic gain control stage and the quadrature phase digital-to-analog converter is operable to provide a quadrature phase DC offset compensation signal for the automatic gain control stage..

Claim 7 (currently amended) A method of determining a signal delay between inputs of first and second low pass filters of a dual mixer stage radio receiver and an output of the receiver's demodulator, the method comprising the steps of:

applying a first known voltage to an input of an in-phase mixer of the second mixer stage;

applying a second known voltage to an input of a quadrature phase mixer of the second mixer stage;

setting the gain of an automatic gain control stage, coupled to the second mixer stage, to a full gain; measuring first in-phase and first quadrature phase components at the output of the demodulator;

decreasing the gain of the automatic gain control stage by a predetermined amount if the value of ~~each~~ either first component is greater than a predetermined maximum threshold value;

storing the first in-phase and quadrature phase components if the value of each component is less than the predetermined maximum threshold value;

applying the negative of the first known voltage to the input of the in-phase mixer;

~~applying the value of the second known voltage to the input of the quadrature phase mixer;~~

measuring second in-phase and second quadrature phase components at the output of the demodulator;

Application number. 09/813,420
Amendment dated August 26, 2004
Reply to office action of February 26, 2004

PATENT

decreasing the gain of the automatic gain control stage by a predetermined amount if the value of each either second component is greater than the predetermined maximum threshold value;

storing the second in-phase and quadrature phase components if the value of each second component is less than the predetermined maximum threshold value; and

using the first and second quadrature phase components to compute the signal delay.

Claim 8 (original) A method of compensating for DC offset voltages present at an input of a low noise amplifier of a dual mixer stage radio receiver, the method comprising the steps of:

determining a signal delay between an output of a second mixer stage of the dual mixer stage radio receiver, said signal delay characterizing in-phase and quadrature phase components of the DC offset voltage present at the input of the low noise amplifier;

using the determined signal delay to separate and define digital representations of the in-phase DC offset voltage component and the quadrature phase DC offset voltage component;

making the digital representation of each of the in-phase and quadrature phase components more positive or more negative if it is more negative or more positive than a predetermined minimum threshold or maximum threshold; and

performing the above sequence of steps a predetermined number of times to reduce the DC offset voltage at the input of the low noise amplifier.

Claim 9 (original) A method of setting signal levels of in-phase and quadrature phase components of a radio receiver between a minimum threshold voltage and a maximum threshold voltage, the method comprising the steps of:

(a) setting the gain of an automatic gain control to a gain value at which the signal levels of the in-phase and quadrature phase components are less than or equal to the maximum threshold voltage;

Application number. 09/813,420
Amendment dated August 26, 2004
Reply to office action of February 26, 2004

PATENT

(b) comparing the signal levels of the in-phase and quadrature phase components to a predetermined minimum threshold value;

(c) increasing the gain of the automatic gain control stage by a predetermined amount; and

(d) repeating steps (b) and (c) until the signal levels of the in-phase and quadrature phase components are greater than or equal to the predetermined minimum threshold value.

Claim 10 (original) A method of compensating for DC offset voltages at inputs of in-phase and quadrature phase low pass filters of a dual mixer stage radio receiver, said method comprising the steps of:

determining a signal delay vector between the inputs of the low pass filters, said signal delay vector characterizing in-phase and quadrature phase components of DC offset voltages at the inputs of the low pass filters;

using the signal delay vector to separate and define in-phase and quadrature phase multiplication factors associated with the in-phase and quadrature phase DC offsets;

incrementally adjusting the signal level of the in-phase component to a more positive or more negative value if the in-phase multiplication factor has a negative or positive value, respectively; and

incrementally adjusting the signal value of the quadrature phase component to a more positive or more negative value if the quadrature phase multiplication factor has a negative or positive value, respectively.